

ONE CARE SOLUTION

WATER DISPENSER

— TECHNICAL SPECIFICATIONS —

MODEL	ONE CARE - N			ONE CARE - NH			ONE CARE - NC			ONE CARE - NHC		
	M 75	M 100	M 150	M 75	M 100	M 150	M 75	M 100	M 150	M 75	M 100	M 150
 Storage Tank - Normal Water	35 L	60 L	80 L	35 L	60 L	80 L	15 L	25 L	45 L	15 L	25 L	45 L
 Storage Tank - Cold Water	-	-	-	-	-	-	15 L	25 L	45 L	15 L	25 L	45 L
 Storage Tank - Hot Water	-	-	-	4 L	4 L	4 L	-	-	-	4 L	4 L	4 L
 No. of Faucets	2	2	2	2	2	2	2	2	2	3	3	3
 No. of Power Cord	1											
 Power Supply (AC 50 Hz)	180 to 260 Volts											
 Heater Power in Watts	1000											
 Purification Method	Any combinations of Reverse Osmosis / Ultraviolet											
 MOC - Housing	Stainless Steel - 0.8 mm Sheet											
 MOC - Normal Water Tank	LLDPE											
 MOC - Cold Water Tank	Stainless Steel 304 - 0.8 mm Sheet											
 MOC - Hot Water Tank	Stainless Steel 304 - 0.8 mm Sheet											
 MOC - Faucets	Brass - Chromium Plated											
 Insulation of Cooling Tank	PUF											
 Dimension of M 75	L 415 x W 415 x H 1350 mm											
 Dimension of M 100	L 480 x W 480 x H 1400 mm											
 Dimension of M 150	L 600 x W 520 x H 1450 mm											
 Compressor Make	Emerson / Tecumseh											
 Compressor Refrigerant	R - 134a											



ONE CARE - N



ONE CARE - NH



ONE CARE - NC



ONE CARE - NHC



PURE
WATER



STAINLESS STEEL
DURABLE BODY



RO / UV
PURIFICATION



HOT & COLD
OPTIONS



RELIABLE
PERFORMANCE